



GoControl WS15Z5-1 WS15Z5-1 Manual

[Home](#) » [GoControl](#) » [GoControl WS15Z5-1 WS15Z5-1 Manual](#) 

Contents

- 1 [GoControl](#)
- 2 [WS15Z5-1](#)
 - 2.1 [SKU: WS15Z5-1](#)
 - 2.2 [Quickstart](#)
 - 2.3 [Important safety information](#)
 - 2.4 [What is Z-Wave?](#)
 - 2.5 [Product Description](#)
 - 2.6 [Prepare for Installation / Reset](#)
 - 2.6.1 [Reset to factory default](#)
 - 2.6.2 [Safety Warning for Mains Powered Devices](#)
 - 2.7 [Inclusion/Exclusion](#)
 - 2.7.1 [Inclusion](#)
 - 2.7.2 [Exclusion](#)
 - 2.8 [Quick trouble shooting](#)
 - 2.9 [Association – one device controls an other device](#)
 - 2.9.1 [Association Groups:](#)
 - 2.10 [Configuration Parameters](#)
 - 2.10.1 [Parameter 3: Night Light](#)
 - 2.10.2 [Parameter 4: Invert Switch](#)
 - 2.11 [Technical Data](#)
 - 2.12 [Supported Command Classes](#)
 - 2.13 [Controlled Command Classes](#)
 - 2.14 [Explanation of Z-Wave specific terms](#)
 - 2.15 [Related Posts](#)

WS15Z5-1

SKU: WS15Z5-1



Quickstart

This is a

On/Off Power Switch

for

U.S. / Canada / Mexico.

To run this device please connect it to your mains power supply.

To add this device to your network execute the following action:

With your Controller in Discovery or Add Mode, tap the switch. The LED will blink slowly when in ADD Mode. You should see an indication on your Controller that the device was added to the network and the LED will stop blinking. The device will appear in the list of Switches. It should display as a switch.

Please refer to the [Manufacturers Manual](#) for more information.

Important safety information

Please read this manual carefully. Failure to follow the recommendations in this manual may be dangerous or may violate the law.

The manufacturer, importer, distributor and seller shall not be liable for any loss or damage resulting from failure to comply with the instructions in this manual or any other material.

Use this equipment only for its intended purpose. Follow the disposal instructions.

Do not dispose of electronic equipment or batteries in a fire or near open heat sources.

What is Z-Wave?

Z-Wave is the international wireless protocol for communication in the Smart Home. This device is suited for use in the region mentioned in the Quickstart section.

Z-Wave ensures a reliable communication by reconfirming every message (**two-way communication**) and every mains powered node can act as a repeater for other nodes (**meshed network**) in case the receiver is not in direct wireless range of the transmitter.



This device and every other certified Z-Wave device can be **used together with any other certified Z-Wave device regardless of brand and origin** as long as both are suited for the same frequency range.

If a device supports **secure communication** it will communicate with other devices secure as long as this device provides the same or a higher level of security. Otherwise it will automatically turn into a lower level of security to maintain backward compatibility.

For more information about Z-Wave technology, devices, white papers etc. please refer to www.z-wave.info.

Product Description

The WS15Z5-1 is a Smart in-wall switch designed providing the ideal mood for every situation for the entire home. Not only can this switch control the connected load, with Central Scene support it can run up to 8 scenes created by the Hub, making the familiar light switch the most versatile Home Automation light switch available. It can essentially control lights and devices throughout the entire home. With Over The Air upgrading supported, this device can be seamlessly updated to the most recent firmware and software features. Finally, as a Z-Wave plus product, its 30% longer range is ideal for easily creating a strong Z-Wave mesh network for an easier installation and more reliable operation.

Prepare for Installation / Reset

Please read the user manual before installing the product.

In order to include (add) a Z-Wave device to a network it **must be in factory default state**. Please make sure to reset the device into factory default. You can do this by performing an Exclusion operation as described below in the manual. Every Z-Wave controller is able to perform this operation however it is recommended to use the primary controller of the previous network to make sure the very device is excluded properly from this network.

Reset to factory default

This device also allows to be reset without any involvement of a Z-Wave controller. This procedure should only be used when the primary controller is inoperable.

To reset the WS15Z5-1 and clear all network information, follow these steps:1. Tap the top of the switch five (5) times.2. Press and hold the bottom of the switch for 15 seconds. The LED will increasingly blink faster to indicate that a Reset is taking place.

Safety Warning for Mains Powered Devices

ATTENTION: only authorized technicians under consideration of the country-specific installation guidelines/norms may do works with mains power. Prior to the assembly of the product, the voltage network has to be switched off and ensured against re-switching.

Inclusion/Exclusion

On factory default the device does not belong to any Z-Wave network. The device needs to be **added to an existing wireless network** to communicate with the devices of this network. This process is called **Inclusion**.

Devices can also be removed from a network. This process is called **Exclusion**. Both processes are initiated by the primary controller of the Z-Wave network. This controller is turned into exclusion respective inclusion mode. Inclusion and Exclusion is then performed doing a special manual action right on the device.

Inclusion

With your Controller in Discovery or Add Mode, tap the switch. The LED will blink slowly when in ADD Mode. You should see an indication on your Controller that the device was added to the network and the LED will stop blinking. The device will appear in the list of Switches. It should display as a switch.

Exclusion

Set the Controller into Removal Mode and follow its instruction to delete the WS15Z5-1 from the Controller. Remove the switch by tapping the paddle 2 times. The LED will begin blinking slowly for 10 seconds indicating that it has been removed. You should see an indication on your Controller that the device was removed from the network.

Quick trouble shooting

Here are a few hints for network installation if things don't work as expected.

1. Make sure a device is in factory reset state before including. In doubt exclude before include.
2. If inclusion still fails, check if both devices use the same frequency.
3. Remove all dead devices from associations. Otherwise you will see severe delays.
4. Never use sleeping battery devices without a central controller.

5. Dont poll FLIRS devices.
6. Make sure to have enough mains powered device to benefit from the meshing

Association – one device controls an other device

Z-Wave devices control other Z-Wave devices. The relationship between one device controlling another device is called association. In order to control a different device, the controlling device needs to maintain a list of devices that will receive controlling commands. These lists are called association groups and they are always related to certain events (e.g. button pressed, sensor triggers, ...). In case the event happens all devices stored in the respective association group will receive the same wireless command wireless command, typically a 'Basic Set' Command.

Association Groups:

Group Number Maximum Nodes Description

Group Number	Maximum Nodes	Description
1	5	Z-Wave Plus Lifeline
2	5	Other Non-Dimming devices
3	5	Dimmers

Configuration Parameters

Z-Wave products are supposed to work out of the box after inclusion, however certain configuration can adapt the function better to user needs or unlock further enhanced features.

IMPORTANT: Controllers may only allow configuring signed values. In order to set values in the range 128 ... 255 the value sent in the application shall be the desired value minus 256. For example: To set a parameter to 200 it may be needed to set a value of 200 minus 256 = minus 56. In case of a two byte value the same logic applies: Values greater than 32768 may needed to be given as negative values too.

Parameter 3: Night Light

The LED Night Light on the WS15Z5-1 will turn OFF when the load attached is turned ON. To make the LED turn ON when the load attached is turned ON.

Size: 1 Byte, Default Value: 0

Setting Description

0	0 – LED OFF when the load is on, and ON when the load is off.
1	1 – LED ON when the load is on, and OFF when the load is off.
2	2 – LED is always on.
3	3 – LED is always off.
4	4 – LED blinks during RF transmissions from or to the device.

Parameter 4: Invert Switch

To change the top of the switch to OFF and the bottom of the switch ON.

Size: 1 Byte, Default Value: 0

Setting Description

0 – 1	0 – Top of switch is ON, bottom of switch is OFF. 1 – Bottom of switch is ON, top of switch is OFF
-------	---

Technical Data

Hardware Platform	ZM5202
Device Type	On/Off Power Switch
Network Operation	Always On Slave
Firmware Version	HW: 255 FW: 1.26
Z-Wave Version	6.51.09
Certification ID	ZC10-17045537
Z-Wave Product Id	0x014F.0x5753.0x3535
Color	White
Neutral Wire Required	ok
Electric Load Type	Incandescent
Z-Wave Scene Type	Central Scene
Frequency	XXfrequency
Maximum transmission power	XXantenna

Supported Command Classes

- Association Grp Info
- Association V2
- Basic V2
- Central Scene V2
- Configuration V3
- Device Reset Locally
- Firmware Update Md V2
- Manufacturer Specific V2
- Powerlevel
- Scene Activation
- Scene Actuator Conf
- Switch All
- Switch Binary
- Version V2
- Zwaveplus Info V2

Controlled Command Classes

- Basic V2

Explanation of Z-Wave specific terms

- **Controller** — is a Z-Wave device with capabilities to manage the network.
Controllers are typically Gateways, Remote Controls or battery operated wall controllers.

- **Slave** — is a Z-Wave device without capabilities to manage the network. Slaves can be sensors, actuators and even remote controls.
- **Primary Controller** — is the central organizer of the network. It must be a controller. There can be only one primary controller in a Z-Wave network.
- **Inclusion** — is the process of adding new Z-Wave devices into a network.
- **Exclusion** — is the process of removing Z-Wave devices from the network.
- **Association** — is a control relationship between a controlling device and a controlled device.
- **Wakeup Notification** — is a special wireless message issued by a Z-Wave device to announces that is able to communicate.
- **Node Information Frame** — is a special wireless message issued by a Z-Wave device to announce its capabilities and functions.

[Manuals+](#)