

Smoke Heat Freeze Detector

2GIG-SMKT8E-345 (eSeries with encrypted signal)

2GIG-SMKT8-345 (non-encrypted signal)



The 2GIG Smoke Heat Freeze Detectors are designed to recognize smoke from common synthetic materials and decrease nuisance alarms from everyday cooking. Using advanced detection algorithms and a sophisticated photo-electric optical sensor, these two detectors meet the new UL standards for the year 2020*.

The new 2GIG Smoke Heat Freeze Detector has been designed to detect fire issues earlier, providing a more accurate and timely notice in the event of smoke or fire.

Key Features:

- Meets new UL217 8th edition and UL268 7th edition requirements.
- Designed to recognize smoke from some synthetic materials.
- Monitors and reports on excessive temperature variations.
- Optical smoke detection chamber for improved smoke detection.
- Rate of Rise alert is sent to the panel and a siren is triggered once the room temperature is 104°F and the temperature rises 15 degrees or more in one minute.
- Extreme high/low temperature alerts.
- Long-lasting battery with projected life of 10 years.
- 2-year product warranty.

* See reverse for new UL standards

2GIG SMOKE HEAT FREEZE DETECTOR SENSOR SPECIFICATIONS & TECHNOLOGY

UL 217 & 268 Smoke Alarm Standards bring 250 new technological changes to traditional smoke detection. Meeting the new UL standards, the 2GIG Smoke Heat & Freeze Detector provides increased performance and better detection of smoke, including smoke from common synthetic materials found in home furnishings. These synthetic materials generally have a faster burn rate reducing escape time from an average of 17 minutes to 3-4 minutes (UL Press Release – February 2018).

Traditional smoke detectors trigger an alarm when any smoke density reached a specific level, which could have just been normal cooking events. The 2GIG Smoke Heat & Freeze Detector uses advanced algorithms and a sophisticated optical chamber to improve the detection of smoke particles created by some synthetic materials, separate from organic smoke associated with normal cooking events. The new technology is designed to trigger an alarm faster when synthetic smoke is detected versus smoke from cooking, adding to safety and peace of mind.

2GIG SMOKE HEAT FREEZE DETECTOR SENSOR SPECIFICATIONS

Ordering Part Number	2GIG-SMKT8-345, 2GIG-SMKT8e-345
Wireless Signal Range	350 ft (106.7m), open air with Wireless Control Panel
Transmitter Frequency	345 MHz
Compatibility	2GIG-SMKT8-345 works with 2GIG Panels 2GIG-SMKT8e-345 works with GC2e and GC3e Panels only
Supervisory Interval	70 minutes
Dimensions (D x H)	4.7 x 2.3 inches (120 x 58 mm)
Weight	0.46 lbs
Audible Alarm	> 85dB (A) at 10ft (3m) minimum
High Temperature Level	134°F +/- 4°F
High Temperature Rate of Rise	Temperature above 104°F and increases 15°F or more in one minute
Low Temperature Level	40°F +/- 4°F. Reset at 45°F +/- 4°F
Operating Temperature	-40° to 100°F (4.4°C to 37.8°C)
Operating Rel. Humidity	15% to 95%, non-condensing
Batteries	2 x CR123A
Regulatory Listing	UL268 7th Edition, CAN/ULC S529 7th Edition, CSFM
Projected Battery Life	10 years
Warranty	2 years

Specification and availability subject to change without notice



2GIG is a registered trademark of Nortek Security & Control LLC. All Rights Reserved.
© 2021 Nortek Security & Control LLC.

P/N: 411852405 - Rev C



5919 Sea Otter Place, Suite 100 • Carlsbad CA 92010 • 760.438.7000 • 800.421.1587

nortekcontrol.com